Amendment dated March 11, 2004

Reply to Office Action dated December 12, 2003

Listing of the Claims:

1. (Currently Amended) A method for fabricating a liquid crystal display (LCD), comprising:

forming a first substrate and a second substrate;

forming patterned spacers on the first substrate;

forming oriented films on the first substrate and on the second substrate;

disposing the first substrate and the second substrate in a facing relationship

wherein the oriented films on the first substrate and on the second substrate contact each other;

radiating light performing an orientation treatment on the oriented films on the first substrate and on the second substrate such that the oriented films bond to orient the films and to bond the first substrate and the second substrate together; and

interposing a liquid crystal between the first substrate and the second substrate.

- 2. (Original) The method of claim 1, wherein the liquid crystal is a smectic liquid crystal.
- 3. (Cancelled)
- 4. (Currently Amended) The method of claim [[3]] 1, wherein the light radiation is performed with radiated light is linearly polarized light.
- 5. (Currently Amended) The method of claim [[3]] 1, wherein the light radiation is performed with radiated light is elliptically polarized light.
- 6. (Currently Amended) The method of claim [[3]] 1, wherein the light radiation is performed with radiated light is UV light.
- 7. (Currently Amended) The method of claim [[3]] 1, wherein the bond of the substrates performing the orientation treatment includes pressing the first substrate and the second substrate together.
- 8. (Original) The method of claim 1, wherein forming a first substrate includes: forming a plurality of crossing gate lines and data lines on the first substrate; forming thin film transistors at each crossing; and

Amendment dated March 11, 2004

Reply to Office Action dated December 12, 2003

forming pixel electrodes that electrically connect to the thin film transistors.

9. (Original) The method of claim 1, wherein the patterned spacers are formed between the pixel electrodes.

10. (Currently Amended) A method for fabricating an LCD, comprising:

forming a first substrate and a second substrate;

forming a first oriented film on the first substrate and a second oriented film on the second substrate;

locating spacers on the first substrate;

disposing the first substrate and the second substrate in a facing relationship such that the spacers form a gap between the first substrate and the second substrate;

performing an orientation treatment radiating light on the first oriented film and on the second oriented film using light radiation and such that the to orient the first and second films and to bond the first substrate and the second substrate are bonded together; and

interposing a liquid crystal between the first substrate and the second substrate.

- 11. (Original) The method of claim 10, wherein the spacers include photo cross-linkable adhesive spacers and ball spacers.
- 12. (Original) The method of claim 10, wherein the liquid crystal is a smectic liquid crystal.
- 13. (Currently Amended) The method of claim 10, wherein the first substrate and the second substrate are pressed together during the radiating light orientation treatment.
- 14. (Currently Amended) The method of claim 10, wherein the <u>radiating</u> light is lineally polarized light or elliptically polarized light.
- 15. (Currently Amended) A method for fabricating a liquid crystal display, comprising: forming a first substrate and a second substrate; forming oriented films on the first substrate and on the second substrate; disposing the first substrate and the second substrate in a facing relationship;

Amendment dated March 11, 2004

Reply to Office Action dated December 12, 2003

performing an orientation treatment radiating light on the oriented films using light radiation such that to orient the films and to bond the first substrate and the second substrate are bonded together; and

interposing a liquid crystal between the first substrate and the second substrate.

- 16. (Original) The method of claim 15, further including locating spacers on the first substrate.
- 17. (Original) The method of claim 16, wherein the spacers are located by depositing and then patterning a spacer material.
- 18. (Original) The method of claim 16, wherein the spacers are located by dispersing photo cross-linkable adhesive spacers on the first substrate.
- 19. (Original) The method of claim 18, wherein ball spacers are located by dispersing ball spacers on the first substrate between the photo cross-linkable adhesive spacers.
- 20. (Currently Amended) The method of claim 15, wherein the <u>radiating</u> light radiation is performed using linearly polarized light.
- 21. (Currently Amended) The method of claim 15, wherein the <u>radiating</u> light radiation is performed using elliptically polarized light.
- 22. (Currently Amended) A liquid crystal display, comprising:
 - a first substrate having patterned spacers;
- a first oriented film, comprised of a light reactive material, over the first substrate and over its patterned spacers, wherein the first oriented film forms a first alignment film;
 - a second substrate;
- a second oriented film, comprised of a light reactive material, over the second substrate, wherein the second oriented film forms a second alignment film; and
 - a liquid crystal,

wherein the first substrate and the second substrate are configured in a facing relationship such that the first alignment film on the patterned spacers contacts the second alignment film, wherein a radiating light on the contacting alignment films bond orients and bonds the first

Amendment dated March 11, 2004

Reply to Office Action dated December 12, 2003

substrate and the second substrate together, wherein a gap exists between portions of the first substrate and portions of the second substrate, and wherein the liquid crystal is disposed in the gap.

- 23. (Original) The liquid crystal display of claim 22 wherein the liquid crystal is a smectic liquid crystal.
- 24. (Previously Presented) The liquid crystal display of claim 22, wherein the light reactive materials of the first substrate and the second substrate react to linearly polarized light.
- 25. (Previously Presented) The liquid crystal display of claim 22, wherein the light reactive materials of the first substrate and the second substrate react to elliptically polarized light.
- 26. (Previously Presented) The liquid crystal display of claim 22, wherein the light reactive materials of the first substrate and the second substrate react to UV light.
- 27. (Original) The liquid crystal display of claim 22, wherein the light reactive materials on the first substrate and on the second substrate are selected from a group consisting of materials with a polyvinylcinnamate lineage, a polyazobenzene lineage, a cellulosecinnamate lineage and a photosensitive polyimide lineage.
- 28. (Previously Presented) The liquid crystal display of claim 22, wherein the patterned spacers are located between pixel electrodes.
- 29. (Currently Amended) A liquid crystal display, comprising:
 - a first substrate;
- a first oriented film, comprised of a light reactive material, over the first substrate, wherein the first oriented film forms a first alignment film;
 - a plurality of spacers on the first substrate;
- a second substrate configured over the plurality of spacers such that the second substrate is disposed away from the first substrate;
- a second oriented film, comprised of a light reactive material, on the second substrate and disposed between the first substrate and the second substrate and in contact with the plurality of spacers, wherein the second oriented film forms a second alignment film; and

Amendment dated March 11, 2004

Reply to Office Action dated December 12, 2003

a liquid crystal between the first substrate and the second substrate,

wherein the first alignment film contacts the second alignment film such that <u>a radiating</u> <u>light on</u> the contacting films <u>bond</u> <u>orients and bonds</u> the first substrate and second substrate together.

- 30. (Previously Presented) The liquid crystal display of claim 29, wherein the plurality of spacers include photo cross-linkable adhesive spacers that bond the first substrate to the second substrate.
- 31. (Previously Presented) The liquid crystal display of claim 29, wherein the plurality of spacers include ball spacers.
- 32. (Original) The method of claim 29, wherein the liquid crystal is a smectic liquid crystal.
- 33. (Previously Presented) The liquid crystal display of claim 29, wherein the light reactive materials of the first substrate and the second substrate react to linearly polarized light.
- 34. (Previously Presented) The liquid crystal display of claim 29, wherein the light reactive materials of the first substrate and the second substrate react to elliptically polarized light.
- 35. (Previously Presented) The liquid crystal display of claim 29, wherein the light reactive materials of the first substrate and the second substrate react to UV light.
- 36. (Previously Presented) The liquid crystal display of claim 29, wherein the light reactive materials of the first substrate and the second substrate are selected from a group consisting of materials with a polyvinylcinnamate lineage, a polyazobenzene lineage, a cellulosecinnamate lineage and a photosensitive polyimide lineage.